

# SAFETY DATA SHEET

## Rechargeable Lithium Ion Batteries A25 / A26 / A27 / A28 / A29 / A30

1	Identification of the product and of the company .....	2
2	Hazards identification.....	3
3	Composition/information on ingredients.....	3
4	First-aid measures .....	4
5	Fire-fighting measures.....	4
6	Accidental release measures .....	5
7	Handling and storage.....	5
8	Exposure controls/personal protection .....	5
9	Physical and chemical properties.....	6
10	Stability and reactivity .....	6
11	Toxicological information .....	6
12	Ecological information.....	6
13	Disposal considerations.....	7
14	Transport information .....	7
15	Regulatory information .....	8
16	Other information .....	8

## 1 Identification of the product and of the company

### *Product details*

Trade name:	Rechargeable lithium ion battery
Electrochemical system:	Lithium ion
Anode (negative):	Graphite based
Cathode (positive):	Lithium cobalt oxide

<i>Type</i>	<i>Watt-hour rating</i>
A25	0.67 Wh
A26	0.44 Wh
A27	0.76 Wh
A28	0.76 Wh
A29	0.44 Wh
A30	0.76 Wh

### *Supplier details*

Wyon AG	
Sägehüslistrasse 15	Tel: +41 71 787 56 25
CH-9050 Appenzell-Steinegg	Fax: +41 71 787 56 12
Switzerland	e-mail: info@wyon.ch

### *Emergency telephone number:*

+41 71 787 56 25

### *Legal Remark (U.S.A.)*

Safety Data Sheets are a sub-requirement of the Occupational Safety and Health Administration (OSHA) Hazard Communication Standard, 29 CFR Subpart 1910.1200. This Hazard Communication Standard does not apply to various subcategories including anything defined by OSHA as an "article". According to OSHA, Article means a manufactured item other than a fluid or particle: (i) which is formed to a specific shape or design during manufacture; (ii) which has end use function(s) dependent in whole or in part upon its shape or design during end use; and (iii) which under normal conditions of use does not release more than very small quantities, e.g., minute or trace amounts of a hazardous chemical (as determined under paragraph (d) of this section), and does not pose a physical hazard or health risk to employees. Because all of our batteries are defined as "articles", they are exempted from the requirements of the Hazard Communication Standard.

### *Legal remark (EU)*

These batteries are no "substances" or "mixtures" according to Regulation (EC) No 1907/2006 EC. Instead they have to be regarded as "articles", no substances are intended to be released during handling. Therefore there is no obligation to supply a "safety data sheet according to Regulation (EC) 1907/2006, Article 31".

*General remark*

The information and recommendations set forth are made in good faith and believed to be accurate as of the date of preparation. Wyon AG makes no warranty, expressed or implied, with respect to this information and disclaims all liabilities from reliance on it.

## 2 Hazards identification

The battery is sealed hermetically. Thus, the ingredients have no hazard potential, except the battery is violated or dismantled.

If in case of mistreatment the ingredients are released, a spontaneously flammable gas mixture may be released under certain circumstances (measures according to chapter 4 to 6).

Attention: If batteries are treated wrong the danger of burns or bursts occurs. Batteries must not be heated above 100°C or incinerated. The battery contents must not get in contact with water. If the negative electrode gets in contact with water or humidity hydrogen gas is formed, which may inflame spontaneously.

## 3 Composition/information on ingredients

*Ingredients:*

Material	CAS No	Contents (% w/w)
Lithium cobaltate	12190-79-3	25 - 45
Graphite	7782-42-5	25 - 45
Organic Solvent	623-53-0 and 96-49-1	5 - 20
Copper	7440-50-8	5 - 10
Polyvinylidene difluoride (PVDF)	24937-79-9	1 - 5
Lithium Salt	21324-40-3	1 - 5
Aluminum	7429-90-5	1 - 5

During charge process a lithium carbon intercalation phase is formed, which is highly flammable and corrosive, but not released under the circumstances of normal usage.

## 4 First-aid measures

Measures at accidental release.

*After inhalation:* Fresh air. Seek for medical assistance.

*After skin contact:* Remove solid particles immediately. Flush affected areas with plenty of water (at least 15 min.). Remove contaminated cloth immediately. Seek for medical assistance.

*After eye contact:* Flush the eye gently with plenty of water (at least 15 min.). Seek for medical assistance.

*After ingestion:* Drink plenty of water. Avoid vomiting. Seek for medical assistance. No trials for neutralization.

## 5 Fire-fighting measures

*Suitable extinguishing media:*

Metal fire extinction powder, rock salt or dry sand shall be used. In case only water is available, it can be used in large amounts.

*Extinguishing media with limited suitability:*

Carbon dioxide (CO<sub>2</sub>) is not suitable. Water in small quantities may have adverse effects.

*Special protection equipment during fire-fighting:*

Contamination cloth including breathing apparatus.

*Special hazard:*

Cells may burst and release electrolyte. At contact of electrolyte with water traces of hydrofluoric acid may be formed. In this case avoid contact and take care for good ventilation.

At contact of charged anode material with water extremely flammable hydrogen gas is generated.

*Attention:*

Do not let used extinguishing media penetrate into surface water or ground water. If necessary, thicken water or foam with suitable solids. Dispose properly.

## 6 Accidental release measures

### *Person related measures:*

Wear personal protective equipment adapted to the situation (protection gloves, face protection, breathing protection).

### *Environment protection measures:*

Bind released ingredients with powder (rock salt, sand). Dispose according to the local law and rules. Avoid leached substances to penetrate into the earth, canalization or water.

### *Treatment for cleaning:*

If battery casing is dismantled, small amounts of electrolyte may leak. Package the battery tightly including ingredients together with lime, sand or rock salt. Then clean with water.

## 7 Handling and storage

### *Guideline for safe handling:*

Always follow the warning information on the batteries and in the manuals of devices. Only use the recommended battery types.

Unpacked batteries shall not lie about in bulk.

Do not swallow batteries.

Do not throw batteries into water.

Do not throw batteries into fire.

Avoid deep discharge.

Do not short-circuit batteries

Use recommended charging time and current.

Do not open or disassemble batteries.

### *Storage:*

Storage preferably at room temperature (approx. 20°C). Avoid large temperature changes. Do not store close to heating devices. Avoid direct sunlight. At higher temperature the electrical performance may be reduced.

Preferred storage at 50% of the nominal capacity.

Storage of unpacked batteries can cause short circuit and heat generation.

Storage category according to TRGS 510:

It is recommended to consider the "Technical Rule for Hazardous Substances TRGS 510 - Storage of hazardous substances in nonstationary containers" and to handle rechargeable lithium ion batteries according to storage category 11 ("combustible solids").

## 8 Exposure controls/personal protection

Under normal conditions (during charge and discharge) release of ingredients does not occur.

## 9 Physical and chemical properties

Specific Gravity (H <sub>2</sub> O=1):	LiCoO <sub>2</sub> : 4.95 Graphite: 2.09-2.2
Melting Point :	LiCoO <sub>2</sub> about 1130 °C
Appearance and Odour:	LiCoO <sub>2</sub> is a black, odourless powder C is a black, odourless powder Organic solvent is a colourless or light yellow liquid with characteristic fruity odour. Lithium salt is a white, crystalline and odourless powder

## 10 Stability and reactivity

Dangerous reactions:  
When heated above 100°C the risk of rupture occurs.

## 11 Toxicological information

Under normal conditions (during charge and discharge) release of ingredients does not occur.  
In case of accidental release see information in chapter 2, 3, 4.

## 12 Ecological information

Wyon lithium ion batteries do not contain heavy metals as defined by the European directives 2006/66/EC Article 21; they comply with the chemical composition requirements of this Directive.

Mercury has not been "intentionally introduced (as distinguished from mercury that may be incidentally present in other materials)" in the sense of the U.S.A. "Mercury-Containing and Rechargeable Battery Management Act" (May 13 1996).

The Regulation on Mercury Content Limitation for Batteries promulgated on 1997-12-31 by the China authorities including the State Administration of Light Industry and the State Environmental Protection Administration defines 'low mercury' as 'mercury content by weight in battery as less than 0.025%', and 'mercury free' as 'mercury content by weight in battery as less than 0.0001%'. And therefore: Wyon lithium ion batteries belong to the category of mercury-free battery (mercury content lower than 0.0001%).

## 13 Disposal considerations

USA: Lithium ion batteries are classified by the federal government as non-hazardous waste and are safe for disposal in the normal municipal waste stream. These batteries, however, do contain recyclable materials and are accepted for recycling by the Rechargeable Battery Recycling Corporation's (RPBC) Battery Recycling Program. Please go to the RPRC website at [www.rbr.org](http://www.rbr.org) for additional information.

In the European Union, manufacturing, handling and disposal of batteries is regulated on the basis of the DIRECTIVE 2006/66/EC OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 6 September 2006 on batteries and accumulators and waste batteries and accumulators and repealing Directive 91/157/EEC. Customers find detailed information on disposal in their specific countries using the web site of the European Portable Batteries Association ([http://www.epbaeurope.net/legislation\\_national.html](http://www.epbaeurope.net/legislation_national.html)).

Importers and users outside EU should consider the local law and rules.

In order to avoid short circuit and heating, used lithium ion batteries **should never be stored or transported in bulk.**

Proper measures against short circuit are:

- Storage of batteries in original packaging
- Coverage of the terminals
- Embedding in dry sand

## 14 Transport information

Rechargeable lithium ion batteries manufactured by Wyon are considered to be UN 3480 Lithium Ion Batteries, and are tested according to 38.3 of the "UN Manual of Tests and Criteria" for compliance with the requirements of IATA DGR packing instruction 965.

Transportations of cells or batteries packed with equipment or contained in equipment have to follow the appropriate regulations for UN3481.

During the transportation of large amounts of batteries by ship, trailer or railway, do not store them in places of high temperature and do not allow them to be exposed to condensation. During the transportation do not allow the packaging to be damaged, as a damage of the packaging may cause fire. In the event packaging is damaged, special procedures must be used including inspection and repackaging if necessary and handle with care.

Code of practice for packaging and shipment of secondary batteries given in IEC 62133: The packaging shall be adequate to avoid mechanical damage during transport, handling and stacking. The materials and pack design shall be chosen so as to prevent the development of unintentional electrical conduction, corrosion of the terminals and ingress of moisture.

## 15 Regulatory information

Marking consideration:

European Union: According to "DIRECTIVE 2006/66/EC OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 6 September 2006 on batteries and accumulators and waste batteries and accumulators and repealing Directive 91/157/EEC" the batteries have to be marked with the crossed bin. Due to the size of the products the battery need not be marked but a symbol measuring at least 1 × 1 cm shall be printed on the packaging.

According to Dangerous Goods Regulations (see 14.) cells or packaging have to be marked with the Watt-hour rating.

International safety standards:

The basis cells are approved according to UL 1642.

Water hazard class:

The regulations of the German Federal Water Management Act (WHG) are not applicable as Lithium ion batteries are articles and not substances, thus there is no risk of water pollution, except the batteries are violated or dismantled.

## 16 Other information

NA